



## Technical Data Sheet

### 100% Wool Felt **Carpet Underlay**

**100% Wool Felt is made from 100% virgin wool giving a totally natural and comfortable feel underfoot. Felt is the best for sound insulation and thermal insulation and the natural flame retardancy of wool is an added benefit.**

<b>Fibre composition:</b>	<b>100% Virgin wool</b>
<b>Nominal weight:</b>	<b>1424g/m<sup>2</sup> (+/- 5%) (42oz/yd<sup>2</sup>)</b>
<b>Nominal thickness:</b>	<b>11.0mm (+/- 10%)</b>
<b>Roll width:</b>	<b>1.37m</b>
<b>Roll length:</b>	<b>11m or 12.5m</b>
<b>Standard roll area:</b>	<b>15.07m<sup>2</sup> or 17.125m<sup>2</sup></b>
<b>Flame retardancy: BS4790:1987 (Hot metal nut test)</b>	<b>100% Wool Felt achieves a low radius of char in accordance with the Hot Metal Nut Test.</b>
<b>BS5808</b>	<b>Passes all aspect of BS5808</b>



**Anglo Recycling Technology Ltd**

Tong Lane, Whitworth

Rochdale, Lancashire, OL12 8BG

Tel: +44 (0)1706 853513 Fax: +44 (0)1706 853625

Email: [info@anglore recycling.com](mailto:info@anglore recycling.com)

Web: [www.anglore recycling.com](http://www.anglore recycling.com)