



## FR56 Carpet Underlay

## Technical Data Sheet

Felt is recommended for Axminster and Wilton carpet where the seams bed in to the felt giving an excellent finish. The FR range is widely used in areas of high traffic such as pubs, nightclubs and hotels. It gives an unmatched mix of value and wear for our contract customers.

<b>Fibre composition:</b>	<b>Jute/wool/mixed fibres (100% recycled)</b>
<b>Nominal weight:</b>	<b>1898g/m<sup>2</sup> (+/- 5%) (56oz/yd<sup>2</sup>)</b>
<b>Nominal thickness:</b>	<b>11/12mm (+/- 0.5mm)</b>
<b>Roll width:</b>	<b>Up to 4.3m (Standard 1.37m)</b>
<b>Roll length:</b>	<b>12.5m/11.0m</b>
<b>Standard roll area:</b>	<b>17.125m<sup>2</sup>/15.07m<sup>2</sup></b>
<b>Flame retardancy: BS4790:1987 (Hot metal nut test)</b>	<b>Endurance FR achieves a 'low radius of effects of ignition' - no more than 20mm against maximum permitted of 35mm for low radius classification.</b>
<b>Static loading: BS4939</b>	<b>Thickness loss after 24 hours loading and 24 hours recovery: Retained 54.7%</b>
<b>Sound Impact: BS2750 Part 8: 1980</b>	<b>Based on FR40: weighted impact sound improvement 24dB</b>
<b>Thermal Resistance: BS4745</b>	<b>2.5 Togs</b>
<b>Other Information:</b>	<b>Our products are tested to the BS5808</b>

