



## Herdwick Carpet Underlay

## Technical Data Sheet

Herdwick wool felt carpet underlay is made from 100% Herdwick wool giving a totally natural and comfortable feel underfoot. Felt is the best for sound insulation and thermal insulation and the natural flame retardancy of wool is an added benefit.

<b>Fibre composition:</b>	<b>100% Herdwick Wool</b>
<b>Nominal weight:</b>	<b>1000g/m<sup>2</sup> (+/- 5%)</b>
<b>Nominal thickness:</b>	<b>10.0mm (+/- 10%)</b>
<b>Roll width:</b>	<b>1.37m</b>
<b>Roll length:</b>	<b>11m or 12.5m</b>
<b>Standard roll area:</b>	<b>15.07m<sup>2</sup> or 17.125m<sup>2</sup></b>
<b>Flame Retardancy: BS4790:1987 (Hot Metal Nut Test)</b>	<b>Herdwick Wool Felt achieves a 'low radius' of char in accordance with the Hot Metal Nut Test.</b>



**Anglo Recycling Technology Ltd**

Tong Lane, Whitworth

Rochdale, Lancashire, OL12 8BG

Tel: +44 (0)1706 853513 Fax: +44 (0)1706 853625

Email: [info@angloreycling.com](mailto:info@angloreycling.com)

Web: [www.angloreycling.com](http://www.angloreycling.com)

*Note: This sheet is for guidance only and is not intended as a product specification*